

3-in-1 fastener instructions

Parts List

Plungers



1 use for bands/bows



2 use for picks

Dies



A use for bands



B use for bows



C use for picks

Changing Plungers and Dies

Plungers



Install Plunger (1 or 2) by inserting into the handle. Remove plunger by pulling firmly away from handle.

Dies



Install orange Die (A, B or C) into the base. Align tab with opening. Remove die by pulling firmly away from base. Push on tab from below if needed.



How to Band Stems

Install Plunger 1 and Die A.

Tip: Overloading stems will exceed staple capacity. Banded stems under 1/4 inch (6.35 mm) in total diameter may need tightening with a needle nose pliers.



Step 1: Lay stems in Die and slide staple (points down) to the bottom of the die channels.



Step 2: Press handle down firmly to band stems together. Pump handle to tighten.



Step 3: Remove stem from die and repeat as necessary.



How to Crimp Bows

Install Plunger 1 and Die B.

Tip: Use wired ribbon for best results.



Step 1: For an adhesive bow, insert bow back sticky side down – otherwise, go to step 2.



Step 2: Loop ribbon back and forth several times.



Step 3: Center looped ribbon in orange Die and slide staple (points down) to bottom of the die channels.



Step 4: Press handle down firmly to crimp staple around bow.



Step 5: Remove bow and arrange to desired look.



How to Fasten Picks

Install Plunger 2 and Die C.

Tip: For best results, use with stems approximately 3/16 inch (4.7mm) in diameter.



Step 1: Hold pick with prongs rounding to the right and insert pointed end of the pick into slot.



Step 2: Slide pick into slot until it can't go any farther.



Step 3: Place stem on right side of pick flush against the back of the Die and center.



Step 4: Press handle down firmly to fasten pick to stem, pump handle to tighten.



Step 5: Slide stem towards you to remove from Die slot.

Whatever you need, we're here for you
Call 866-348-5661 or visit www.fiskars.com